



## Introduction

The Atlona AT-OME-SR21 is an HDBaseT receiver and 4K/UHD scaler with a local HDMI input. Part of the Omega™ Series of integration products for modern AV communications and collaboration, the OME-SR21 receives HDBaseT for video up to 4K/60 4:2:0, plus embedded audio, control, Ethernet, and USB over distances up to 330 feet (100 meters). The HDMI input supports video up to UHD/60 4:4:4. The OME-SR21 is HDCP 2.2 compliant and features 4K/60 upscaling and downscaling with frame rate conversion. Additionally, it receives USB over HDBaseT and includes a USB 2.0 hub for integration with PCs, cameras, microphones, speakers, DSPs, and touch or interactive displays. The OME-SR21 is ideal for 4K presentation applications with Omega, HDVS-200, or UHD-EX Series transmitters, as well as Atlona AV presentation switchers with HDBaseT outputs, local HDMI sources, and the Gain™ Series amplifiers.

The OME-SR21 combines the benefits of 4K/UHD scaling, auto-switching for HDBaseT and HDMI inputs, integrated display control, USB extension<sup>(1)</sup>, and more. It incorporates many popular integration convenience features, while delivering excellent performance and value for 4K presentation and video conferencing applications. The OME-SR21 can remotely power an Atlona HDBaseT transmitter through Power over Ethernet (PoE). For additional integration convenience, the OME-SR21 features audio de-embedding, integrated two-port Ethernet switch, contact closure ports for controlling a motorized screen or display lift, internal video test patterns for setup and troubleshooting, and remote management with AMS (Atlona Management System).

## Applications

- Complete system integration for video conferencing**  
 The OME-SR21 and an Omega Series switcher/transmitter provide a compact, yet comprehensive and cost-effective integration solution. USB extension makes this combination ideal for soft codec and web-based conferencing applications, with the ability to integrate with PCs, cameras, speakerphones, and microphones.
- Larger system applications**  
 The OME-SR21 is ideal for extending AV and control, from a switcher in an equipment rack to a remote display. Built-in 4K scaling optimizes content for 4K and HD displays.

## Key Features

### HDBaseT receiver with local HDMI input

- HDBaseT input receives AV, power, control, USB, and Ethernet up to 330 feet (100 meters) @ 1080p with CAT5e/6 or 4K/UHD using CAT6a/7 cable.
- HDMI input is ideal for a wireless gateway, PC, video conferencing codec, or media player installed near a display.

### 4K/UHD downscaling and upscaling

- Preserves color and spatial detail when down-converting 4K content to 1080p or vice versa.
- Ideal for presentation applications where content is to be viewed on a variety of 4K and HD displays.
- Also ideal for down-scaling to 1080p for hardware video conferencing codecs.

### USB 2.0 hub and extension over HDBaseT<sup>(1)</sup>

- USB type B interface for connection to a host PC, plus two USB type A ports for peripheral devices such as cameras, soundbars, or touch displays.
- Provides an ideal USB integration solution for software video conferencing and other applications.

### Audio de-embedding

- De-embeds two channel PCM audio from any video source to a balanced, analog audio output.
- Independent volume and mute controls for embedded and de-embedded two-channel PCM audio, plus five-band EQ for the analog audio output.

### Dual Ethernet ports and integrated network switch

- Allows a single connection to an AV LAN for IP control of a display and the OME-SR21 (plus transmitter or switcher over HDBaseT).
- Simplify system design and integration with just one network drop for AV system control.

### Contact closure for screen or display lift control

- Dry contact closure triggers electronic screen or lift operation based on active or standby mode of the switcher/scaler.
- Automates screen or lift activation at system power-up; eliminates need for a separate AV control system.

## Specifications

Video	
HDMI	2.0
HDCP	2.2
UHD/HD/SD	4096x2160@60 <sup>(2)</sup> /50/30/25/24Hz, 3840x2160@60 <sup>(2)</sup> /50/30/25/24Hz, 1080p@60/59.9/50/30/29.97/25/24/23.98Hz, 1080i@30/29.97/25Hz, 720p@60/59.94/50Hz, 576p@50Hz, 576i@25Hz, 480p@60/59.96Hz, 480i@30Hz
VESA	2560×1600, 2048×1536, 1920×1200, 1680×1050, 1600×1200, 1440×900, 1400×1050, 1280×1024, 1280×800, 1366×768, 1360×768, 1152×864, 1024×768, 800×600, 640×480

Video	
Scaler Up/Down	1024x768p60, 1280x720p50, 1280x720p60, 1280x768p60, 1280x800p60, 1360x768p60, 1600x1200p60, 1920x1080p24, 1920x1080p25, 1920x1080p50, 1920x1080p60, 1920x1200p60, 2048x1080p60, 3840x2160p24, 3840x2160p25, 3840x2160p30, 3840x2160p50, 3840x2160p60, 4096x2160p24, 4096x2160p25, 4096x2160p30, 4096x2160p50, 4096x2160p60
Color Space	YUV, RGB
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0
Color Depth	8-bit, 10-bit, 12-bit

Audio	
HDMI Pass-Through Formats	PCM 2.0, LPCM 5.1, LPCM 7.1, Dolby® Digital, Dolby Digital Plus™, Dolby TrueHD, Dolby Atmos®, DTS® Digital Surround™, DTS-HD Master Audio™, and DTS:X®
Bit Rate	24 Mbits/s max
<b>Analog Audio</b>	
Format	Stereo 2-Channel
Balanced Output	+4 dBu nominal gain, +20 dB headroom
Frequency Response	20 Hz to 20 kHz, ± 0.5 dB
Impedance	150 Ω
Stereo channel separation	> 90 dB
THD+N	< 0.03% at 20 Hz to 20 kHz
SNR	> 90 dB at 1 kHz, zero clipping @ 0 dBFS, unweighted
EQ	5 band, 63Hz, 85Hz, 250Hz, 1kHz, 4kHz
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz

USB	
Signal	2.0
Maximum Data Rate	120 Mbps

Control	
RS-232	1-way connected display control 2-way device control and monitoring Supported baud rates: 2400, 4800, 9600, 19200, 38400, 57600, 115200
CEC Support	Yes
Relay	Normally open (NO), adjustable Toggle and Pulse modes Electrical rating: 48V@1A

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI IN/OUT	15	5	30	10
CAT5e	295	90	330	100
CAT6/6a/7	330	100	330	100

Connectors, Controls, and Indicators	
HDMI IN	1 - Type A, 19-pin female
HDBaseT IN	1 - RJ45, female
HDMI OUT	1 - Type A, 19-pin female
USB HUB	2 - Type A, 4-pin female
USB HOST	1 - Type B, female
AUDIO OUT	1 - 5-pin captive screw, balanced / unbalanced 2-channel
RELAY	1 - 3-pin captive screw
RS-232	2 - 3-pin captive screw (bidirectional)
LAN	2 - RJ45, 100Base-T
DC 24V	1 - 4-pin, mini-DIN locking connector
PWR indicator	1 - LED, green
LINK indicator	1 - LED, yellow
<b>Control Buttons:</b> DEVICE IP, INPUT, PATTERN IP MODE, RESET	3 - momentary, tact-type 2 - momentary, recessed
<b>Function Indicators:</b> IP MODE, RESET	2 - LED, green

Temperature	Fahrenheit	Celsius
Operating	32 to 122	0 to 50
Storage	-4 to 140	-20 to 60
Humidity (RH)	20% to 60%, non-condensing	

Power	
Consumption	17.6 W
Supply	Input: 100 - 240 V AC, 50/60 Hz Output: 24 V / 2.7A DC

Dimensions	Inches	Millimeters
H x W x D	1.02 x 8.62 x 5.98	26 x 219 x 152

Weight	Pounds	Kilograms
Device	1.96	0.89

Certification	
Device	CE, FCC, UL

## Accessories

SKU	Description
AT-LC-H2H-1M	LinkConnect HDMI to HDMI Cable
AT-LC-H2H-2M	LinkConnect HDMI to HDMI Cable
AT-LC-H2H-3M	LinkConnect HDMI to HDMI Cable

- 1 This receiver is not compatible with the Atlona HDVS-300 system for USB extension.
- 2 4K/UHD @ 60Hz is limited to 4:2:0 over HDBaseT, 4K/UHD@60Hz 4:4:4 is available via local HDMI